


# CEWELD AA R610

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                  |                      |                    |                         |      |      |          |      |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|----------------------|--------------------|-------------------------|------|------|----------|------|
| TYPE                                               | Seamless micro alloyed rutile cored wire with slag for M21                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                  |                      |                    |                         |      |      |          |      |
| ANWENDUNGEN                                        | Offshore, Shipbuilding, pressure vessels, orbital pipe work respecting the NACE requirements.<br>Steels with yield strength up to 620 MPa (90 ksi).                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                  |                      |                    |                         |      |      |          |      |
| EIGENSCHAFTEN                                      | Very good modeling ability, therefore excellent all-position welding with higher currents. For use down to -40 °C (- 40 °F) .. Particularly suitable for MAG-orbital welding and for weldings on ceramics in all positions. Low spatter loss, and remarkable easy slag removal.                                                                                                                                                                                                                                                                                                                           |                                  |                      |                    |                         |      |      |          |      |
| KLASSIFIKATION                                     | AWS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | A 5.29: E101T1-K2M H4            |                      |                    |                         |      |      |          |      |
|                                                    | EN ISO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 18276-A: T 62 4 Mn1Ni P M21 1 H5 |                      |                    |                         |      |      |          |      |
|                                                    | F-nr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 6                                |                      |                    |                         |      |      |          |      |
|                                                    | FM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2                                |                      |                    |                         |      |      |          |      |
| GEEIGNET FÜR                                       | <b>Reh ≤ 620 MPa ISO 15608: ~3.1, 2.2</b><br>1.8864, 1.8873, 1.8881, 1.8928, 1.8977, 1.8924, 1.8909, 1.8984, 1.8926, 1.8904, 1.8986<br>S500Q-S620Q, S500QL-S620QL, L485MB-L555MB, L485QB-L555QB, 620 M, PAS 460-550<br>ASTM A 572 Gr. 65; A 633 Gr. E; A 738 Gr. A; A 852;<br>API 5 L X70, X80, X70Q, X80Q<br>alform 500 M, 550 M, 600 M, aldur 550 Q, Dillimax 550, Dillimax 500, Domex 500, Domex 550                                                                                                                                                                                                   |                                  |                      |                    |                         |      |      |          |      |
| ZULASSUNGEN                                        | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                  |                      |                    |                         |      |      |          |      |
| SCHWEISSPOSITIONEN                                 | <div></div> |                                  |                      |                    |                         |      |      |          |      |
| TYPISCHE CHEMISCHE ANALYSE DES SCHWEISSMETALLS (%) | C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Si                               | Mn                   | P                  | S                       | Cr   | Ni   | Mo       | Cu   |
|                                                    | 0.062                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.55                             | 1.6                  | 0.006              | 0.014                   | 0.02 | 0.98 | 0.012    | 0.07 |
| MECHANISCHE GÜTEWERTE                              | Heat Treatment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | R <sub>P0,2</sub> (MPa)          | R <sub>m</sub> (MPa) | A <sub>5</sub> (%) | Impact Energy (J) ISO-V |      |      | Hardness |      |
|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                  |                      |                    | -40°C                   |      |      |          |      |
|                                                    | As Welded                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 635                              | 715                  | 28                 | 105                     |      |      | HRc      |      |
| RÜCKTROCKNUNG                                      | Not required                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                  |                      |                    |                         |      |      |          |      |
| GAS ACC. EN ISO 14175                              | M21                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                  |                      |                    |                         |      |      |          |      |



# CEWELD AA R610

AA R610 1,2MM

| Packaging | KG/unit  | EanCode       |
|-----------|----------|---------------|
| D-200     | 20 (4x5) | 8720663423702 |
| K-300     | 16       | 8720663423719 |