

CEWELD Ceramic Backing strip Ø shaped

TYPE Ceramic backing Round

APPLICATIONS This ceramic backing strip offer special economic advantages for submerged arc welding and MAG welding with solid wires or metal- cored wires in the downhand position as well for positional MAG welding using rutile cored wires with fast freezing slag.

PROPRIÉTÉS Available in the dimensions:

Ø (mm)	Longueur (mm)
6	600
8	600
10	600
12	600
15	600

CLASSIFICATION

CONVIENT POUR one side welding with high currents in shipbuilding, pressure vessel fabrication, machine construction, crane building, tank, and general steel building.

AGRÉMENTS


POSITIONS DE SOUDAGE



PROPRIÉTÉS MÉCANIQUES

ETUVAGE Not required

GAS ACC. EN ISO 14175



CEWELD Ceramic Backing strip Ø shaped

CERAMIC BACKING STRIP Ø SHAPED Ø 10MM

Packaging	KG/unit	EanCode
0,6	60 meters per box	8720663410856

CERAMIC BACKING STRIP Ø SHAPED Ø 12MM

Packaging	KG/unit	EanCode
0,6	54 meters per box	8720663410863

CERAMIC BACKING STRIP Ø SHAPED Ø 15MM

Packaging	KG/unit	EanCode
0,6	42 meters per box	8720663410870

CERAMIC BACKING STRIP Ø SHAPED Ø 6MM

Packaging	KG/unit	EanCode
0,6	90 meters per box	8720663410832

CERAMIC BACKING STRIP Ø SHAPED Ø 8MM

Packaging	KG/unit	EanCode
0,6	72 meters per box	8720663410849